

SAFETY DATA SHEET

LIQUITEX PROFESSIONAL SPRAY SATIN VARNISH

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

1. Identification

Product identifier

Product name LIQUITEX PROFESSIONAL SPRAY SATIN VARNISH
Product number 3013646645013

Recommended use of the chemical and restrictions on use

Application Varnish for Acrylic Painting
Uses advised against No specific uses advised against are identified.

Details of the supplier of the safety data sheet

Supplier ColArt Americas Inc.
11 Constitution Avenue
Piscataway
New Jersey 08855 - 1396
USA
1-732-562-0770
R.Enquiries@colart.co.uk

Contact Person Regulatory Manager

Manufacturer ColArt International SA
5 Rue Rene Panhard
Z.I .Nord
72021 Le Mans Cedex 2
+33 2 43 83 83 00

Emergency telephone number

Emergency telephone For health information only call 1-800-628-3385 Piscataway NJ 08855.


2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Aerosol 1 - H222, H229
Health hazards Not Classified
Environmental hazards Not Classified

Label elements

Pictogram



Signal word Danger

Hazard statements H222 Extremely flammable aerosol.
H229 Pressurized container: may burst if heated.

Precautionary statements P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

LIQUITEX PROFESSIONAL SPRAY SATIN VARNISH

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

ACETONE	1-5%
CAS number: 67-64-1	REACH registration number: 01-2119471330-49-xxxx

Classification

Flam. Liq. 2 - H225
Eye Irrit. 2 - H319
STOT SE 3 - H336

METHANOL	<1%
CAS number: 67-56-1	REACH registration number: 01-2119433307-44-xxxx

Classification

Flam. Liq. 2 - H225
Acute Tox. 3 - H301
Acute Tox. 3 - H311
Acute Tox. 3 - H331

TRIETHYLAMINE	<1%
CAS number: 121-44-8	

Classification

Flam. Liq. 2 - H225
Acute Tox. 4 - H302
Acute Tox. 3 - H311
Acute Tox. 3 - H331
Skin Corr. 1A - H314
Eye Dam. 1 - H318
STOT SE 3 - H335

The Full Text for all Hazard Statements are Displayed in Section 16.

4. First-aid measures

Description of first aid measures

General information	If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms are severe or persist.
Ingestion	Rinse mouth thoroughly with water. Get medical advice/attention if you feel unwell. Do not induce vomiting unless under the direction of medical personnel.
Skin Contact	Rinse with water.

LIQUITEX PROFESSIONAL SPRAY SATIN VARNISH

Eye contact	Rinse with water. Get medical attention if any discomfort continues.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Spray/mists may cause respiratory tract irritation.
Ingestion	Due to the physical nature of this product, it is unlikely that ingestion will occur.
Skin contact	Repeated exposure may cause skin dryness or cracking.
Eye contact	May be slightly irritating to eyes. May cause discomfort.

Indication of immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media	The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant.
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

Advice for firefighters

Protective actions during firefighting	Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.
---	---

Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.
--	--

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Evacuate area. Risk of explosion. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated.
-----------------------------	--

Environmental precautions

Environmental precautions	Avoid discharge into drains or watercourses or onto the ground.
----------------------------------	---

LIQUITEX PROFESSIONAL SPRAY SATIN VARNISH

Methods and material for containment and cleaning up

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Do not allow material to enter confined spaces, due to the risk of explosion. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions

Keep out of the reach of children. Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Avoid exposing aerosol containers to high temperatures or direct sunlight. The product is flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Avoid contact with eyes. Avoid inhalation of vapors and spray/mists.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Storage precautions

Store locked up. Keep away from oxidizing materials, heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Protect from sunlight. Do not store near heat sources or expose to high temperatures. Do not expose to temperatures exceeding 50°C/122°F.

Storage class

Chemical storage.

Specific end uses(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

8. Exposure Controls/personal protection

Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation.

Eye/face protection

Avoid contact with eyes. Large Spillages: Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.

Hand protection

No specific hand protection recommended.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact.

LIQUITEX PROFESSIONAL SPRAY SATIN VARNISH

Hygiene measures	Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.
Respiratory protection	No specific recommendations. Provide adequate ventilation. Large Spillages: If ventilation is inadequate, suitable respiratory protection must be worn.
Environmental exposure controls	Keep container tightly sealed when not in use. Avoid release to the environment.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Aerosol.
Color	Colorless.
Odor	Organic solvents.
Flash point	<40°C
Upper/lower flammability or explosive limits	: 1.8
Auto-ignition temperature	> 400°C
Comments	Information given is applicable to the major ingredient.

10. Stability and reactivity

Reactivity	There are no known reactivity hazards associated with this product.
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
Possibility of hazardous reactions	The following materials may react strongly with the product: Oxidizing agents.
Conditions to avoid	Avoid exposing aerosol containers to high temperatures or direct sunlight. Pressurised container: may burst if heated
Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀)	Based on available data the classification criteria are not met.
ATE oral (mg/kg)	18,932.22

Acute toxicity - dermal

Notes (dermal LD₅₀)	Based on available data the classification criteria are not met.
ATE dermal (mg/kg)	36,055.96

Acute toxicity - inhalation

LIQUITEX PROFESSIONAL SPRAY SATIN VARNISH

Notes (inhalation LC₅₀)	Based on available data the classification criteria are not met.
ATE inhalation (gases ppm)	230,384.41
ATE inhalation (vapours mg/l)	360.56
ATE inhalation (dusts/mists mg/l)	164.56
<u>Skin corrosion/irritation</u>	
Animal data	Based on available data the classification criteria are not met.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Based on available data the classification criteria are not met.
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	Based on available data the classification criteria are not met.
<u>Skin sensitisation</u>	
Skin sensitisation	Based on available data the classification criteria are not met.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Based on available data the classification criteria are not met.
<u>Carcinogenicity</u>	
Carcinogenicity	Based on available data the classification criteria are not met.
IARC carcinogenicity	None of the ingredients are listed or exempt.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	Not classified as a specific target organ toxicant after a single exposure.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
<u>Aspiration hazard</u>	
Aspiration hazard	Based on available data the classification criteria are not met.
<u>General information</u>	
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Spray/mists may cause respiratory tract irritation.
Ingestion	Due to the physical nature of this product, it is unlikely that ingestion will occur.
Skin Contact	Repeated exposure may cause skin dryness or cracking.
Eye contact	May be slightly irritating to eyes. May cause discomfort.
Acute and chronic health hazards	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Prolonged or repeated exposure to vapors in high concentrations may cause the following adverse effects: Nausea, vomiting. Headache. Gas or vapor in high concentrations may irritate the respiratory system.
Route of entry	Ingestion Inhalation Skin and/or eye contact

LIQUITEX PROFESSIONAL SPRAY SATIN VARNISH

Target Organs	No specific target organs known.
Medical Symptoms	Symptoms following overexposure may include the following: Headache. Dizziness. Arrhythmia, (deviation from normal heart beat).

12. Ecological Information

Ecotoxicity	Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.
Toxicity	
Toxicity	Based on available data the classification criteria are not met.
Persistence and degradability	
Persistence and degradability	The degradability of the product is not known.
Bioaccumulative potential	
Bio-Accumulative Potential	No data available on bioaccumulation.
Mobility in soil	
Mobility	The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.
Other adverse effects	
Other adverse effects	None known.

13. Disposal considerations

Waste treatment methods

General information	The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Waste class	14 06 03* - waste aerosol propellants, other solvents and solvent mixtures

14. Transport information

UN Number

UN No. (DOT)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950

UN proper shipping name

Proper shipping name (DOT)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS

Transport hazard class(es)

LIQUITEX PROFESSIONAL SPRAY SATIN VARNISH

IMDG Class 2.1

ICAO class/division 2.1

Transport labels



Environmental hazards

Environmentally Hazardous Substance

No.

Special precautions for user

EmS F-D, S-U

15. Regulatory information

Regulatory Status

This product has been evaluated by a toxicologist and labelled for acute and chronic health hazards in accordance with the Labelling of Hazardous Art Materials Regulation and Federal Regulation 16 CFR 1500.14 of the Federal Hazardous Substances Act. This product conforms to ASTM D-4236 Standard Practice for Labelling Art Materials for Chronic Adverse health effects.

This product has been certified by ACMI (Artists Craft Material Institute, Inc.) to carry the CL (Cautionary Labelling) Seal, meaning the health warnings and safe use instructions on the label should be followed.

DANGER: EXTREMELY FLAMMABLE. VAPOR HARMFUL.

Contains: DIMETHYL ETHER

PRECAUTIONS: Do not smoke when using. Avoid contact with heat, sparks and open flame. Vapors can ignite explosively. If using indoors turn off all pilot lights. Use only with adequate ventilation. WARNING: CONTENTS UNDER PRESSURE. Do not puncture or incinerate or expose to temperatures above 120° F (50° C). KEEP OUT OF REACH OF CHILDREN.

FIRST AID TREATMENT: If inhalation symptoms occur, move to fresh air. If symptoms persist, see a physician.

For Health information only call 1-800-628-3385 Piscataway NJ 08855.

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are listed or exempt.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

None of the ingredients are listed or exempt.

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are listed or exempt.

SARA 313 Emission Reporting

None of the ingredients are listed or exempt.

CAA Accidental Release Prevention

None of the ingredients are listed or exempt.

LIQUITEX PROFESSIONAL SPRAY SATIN VARNISH

FDA - Essential Chemical

None of the ingredients are listed or exempt.

FDA - Precursor Chemical

None of the ingredients are listed or exempt.

SARA (311/312) Hazard Categories

None of the ingredients are listed or exempt.

OSHA Highly Hazardous Chemicals

None of the ingredients are listed or exempt.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

None of the ingredients are listed or exempt.

California Air Toxics "Hot Spots" (A-I)

None of the ingredients are listed or exempt.

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed or exempt.

California Directors List of Hazardous Substances

None of the ingredients are listed or exempt.

Massachusetts "Right To Know" List

None of the ingredients are listed or exempt.

Rhode Island "Right To Know" List

None of the ingredients are listed or exempt.

Minnesota "Right To Know" List

None of the ingredients are listed or exempt.

New Jersey "Right To Know" List

None of the ingredients are listed or exempt.

Pennsylvania "Right To Know" List

None of the ingredients are listed or exempt.

Inventories

US - TSCA

None of the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

16. Other information

Training advice	Read and follow manufacturer's recommendations.
Revision date	8/17/2015
Revision	2
Supersedes date	7/14/2015

LIQUITEX PROFESSIONAL SPRAY SATIN VARNISH

Hazard statements in full

H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapor.
H229 Pressurized container: may burst if heated.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.