

SAFETY DATA SHEET
LIQUITEX ARTISTS' ACRYLIC SOFT BODY COLOUR- Transparent Mixing White
According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

1. Identification**Product identifier**

Product name LIQUITEX ARTISTS' ACRYLIC SOFT BODY COLOUR- Transparent Mixing White
Product number D011967

Recommended use of the chemical and restrictions on use

Application Fine Art Painting

Details of the supplier of the safety data sheet

Supplier ColArt Americas Inc.
11 Constitution Avenue
Piscataway
New Jersey 08855 - 1396
USA
1-732-562-0770
R.Enquiries@colart.co.uk

Contact Person Regulatory Manager

Emergency telephone number

Emergency telephone For health information only call 1-800-628-3385 Piscataway NJ 08855.

2. Hazard(s) identification**Classification of the substance or mixture**

Physical hazards Not Classified
Health hazards Not Classified
Environmental hazards Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

Label elements**Pictogram**

Signal word Warning

Hazard statements H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements P273 Avoid release to the environment.
P391 Collect spillage.
P501 Dispose of contents/container in accordance with national regulations.

3. Composition/information on ingredients**Mixtures**

LIQUITEX ARTISTS' ACRYLIC SOFT BODY COLOUR- Transparent Mixing White

ZINC OXIDE		10-30%
CAS number: 1314-13-2	REACH registration number: 01-2119463881-32-xxxx	
M factor (Acute) = 1	M factor (Chronic) = 1	
Classification		
Aquatic Acute 1 - H400		
Aquatic Chronic 1 - H410		
Polyethylene glycol octylphenyl ether		
CAS number: 9036-19-5		1-5%
Classification		
Aquatic Chronic 3 - H412		

The Full Text for all Hazard Statements are Displayed in Section 16.

Composition comments -

4. First-aid measures

Description of first aid measures

Inhalation	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention if any discomfort continues.
Skin Contact	Remove affected person from source of contamination. Get medical attention if irritation persists after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

Most important symptoms and effects, both acute and delayed

Inhalation	No specific symptoms known.
Ingestion	No specific symptoms known.
Skin contact	No specific symptoms known.
Eye contact	May cause temporary eye irritation.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

Advice for firefighters

Protective actions during firefighting No specific firefighting precautions known.

6. Accidental release measures

Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

LIQUITEX ARTISTS' ACRYLIC SOFT BODY COLOUR- Transparent Mixing White

Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses.

7. Handling and storage

Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes.

Conditions for safe storage, including any incompatibilities

Storage precautions Keep only in the original container. Store at moderate temperatures in dry, well ventilated area.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

ZINC OXIDE

Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ total dust
 Long-term exposure limit (8-hour TWA): ACGIH 2 mg/m³ respirable fraction
 Short-term exposure limit (15-minute): ACGIH 10 mg/m³ respirable fraction
 Long-term exposure limit (8-hour TWA): OSHA 5 mg/m³ fume
 Long-term exposure limit (8-hour TWA): OSHA 5 mg/m³ respirable fraction

OSHA = Occupational Safety and Health Administration.

ACGIH = American Conference of Governmental Industrial Hygienists.

Exposure controls

Appropriate engineering controls No specific ventilation requirements.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.

Hand protection No specific hand protection noted.

Other skin and body protection No specific recommendations

Hygiene measures Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance Paste

Color White.

Odor Characteristic.

pH pH (concentrated solution): 9-10

LIQUITEX ARTISTS' ACRYLIC SOFT BODY COLOUR- Transparent Mixing White

Initial boiling point and range	> 100°C @ 760 mm Hg
Vapour density	> 1
Relative density	1.2 - 1.5 @ 20°C
Solubility(ies)	Miscible with water
Other information	Not available.

10. Stability and reactivity

Stability	Stable at normal ambient temperatures.
Conditions to avoid	Avoid excessive heat for prolonged periods of time.
Hazardous decomposition products	Fire creates: Carbon monoxide (CO). Carbon dioxide (CO ₂).

11. Toxicological information

Information on toxicological effects

Acute toxicity - dermal

Notes (dermal LD₅₀) Not determined.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Not determined.

General information	This product has low toxicity. Only large quantities are likely to have adverse effects on human health.
Ingestion	May cause discomfort if swallowed.
Skin Contact	Slightly irritating.
Eye contact	Irritating to eyes.
Acute and chronic health hazards	No specific health hazards known.
Route of entry	Skin and/or eye contact.
Medical Symptoms	Irritation of eyes and mucous membranes.

12. Ecological Information

Ecotoxicity The product contains substances which are toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

Toxicity

Acute toxicity - fish Not determined.

Acute toxicity - aquatic invertebrates Not determined.

Acute toxicity - aquatic plants Not determined.

Acute toxicity - microorganisms Not determined.

Persistence and degradability

LIQUITEX ARTISTS' ACRYLIC SOFT BODY COLOUR- Transparent Mixing White

Persistence and degradability The degradability of the product is not known.

Mobility in soil

Adsorption/desorption coefficient Not determined.

13. Disposal considerations

Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

14. Transport information

UN Number

UN No. (DOT) 3082

UN No. (IMDG) 3082

UN No. (ICAO) 3082

UN proper shipping name

Proper shipping name (DOT) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (zinc oxide)

Proper shipping name (IMDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (zinc oxide)


Proper shipping name (ICAO) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (zinc oxide)

Transport hazard class(es)

IMDG Class 9

ICAO class/division 9

Transport labels



Packing group

DOT pack group III

IMDG packing group III

ICAO packing group III

Environmental hazards

Environmentally Hazardous Substance



15. Regulatory information

LIQUITEX ARTISTS' ACRYLIC SOFT BODY COLOUR- Transparent Mixing White

Regulatory Status

This product has been evaluated by a toxicologist and labelled for acute and chronic health hazards in accordance with the Labelling of Hazardous Art Materials Regulation and Federal Regulation 16 CFR 1500.14 of the Federal Hazardous Substances Act. This product conforms to ASTM D-4236 Standard Practice for Labelling Art Materials for Chronic Adverse health effects.

This product has been certified by ACMI (Artists Craft Material Institute, Inc.) to carry the AP (Approved Product) Seal, meaning this product bears no chronic or acute human health hazards.

16. Other information

Revision date 7/23/2015

Revision 5

Supersedes date 7/13/2015

Hazard statements in full H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.