

# SAFETY DATA SHEET

## LIQUITEX SOLUVAR GLOSS VARNISH

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

### 1. Identification

#### Product identifier

**Product name** LIQUITEX SOLUVAR GLOSS VARNISH

**Product number** 63111

#### Recommended use of the chemical and restrictions on use

**Application** Varnish for Oil Painting Varnish for Acrylic Painting

**Uses advised against** No specific uses advised against are identified.

#### Details of the supplier of the safety data sheet

**Supplier** ColArt Americas Inc.  
11 Constitution Avenue  
Piscataway  
New Jersey 08855 - 1396  
USA  
1-732-562-0770  
R.Enquiries@colart.co.uk

**Contact Person** Regulatory Manager

#### Manufacturer

#### Emergency telephone number

**Emergency telephone** For health information only call 1-800-628-3385 Piscataway NJ 08855.

### 2. Hazard(s) identification

#### Classification of the substance or mixture


**Physical hazards** Flam. Liq. 3 - H226

**Health hazards** Skin Sens. 1 - H317 Repr. 2 - H361d STOT RE 1 - H372

**Environmental hazards** Aquatic Chronic 2 - H411

#### Label elements

##### Pictogram



##### Signal word

Danger

##### Hazard statements

H226 Flammable liquid and vapor.  
H317 May cause an allergic skin reaction.  
H361d Suspected of damaging the unborn child.  
H372 Causes damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.

## LIQUITEX SOLUVAR GLOSS VARNISH

**Precautionary statements**

P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.  
 P261 Avoid breathing vapor/spray.  
 P264 Wash contaminated skin thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P273 Avoid release to the environment.  
 P302+P352 If on skin: Wash with plenty of water.  
 P308+P313 If exposed or concerned: Get medical advice/attention.  
 P403+P235 Store in a well-ventilated place. Keep cool.  
 P405 Store locked up.  
 P501 Dispose of contents/container in accordance with national regulations.

**Contains** Stoddard solvent, Toluene

### Other hazards

This product does not contain any substances classified as PBT or vPvB.

### 3. Composition/information on ingredients

#### Mixtures

<b>Stoddard solvent</b>	<b>30-60%</b>
CAS number: 8052-41-3	
<b>Classification</b> Flam. Liq. 3 - H226 STOT RE 1 - H372 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	
<b>Alkane, C9-12 iso-</b>	<b>10-30%</b>
CAS number: 90622-57-4                      REACH registration number: 01-2119471991-29xxx	
<b>Classification</b> Flam. Liq. 3 - H226 Asp. Tox. 1 - H304 Aquatic Chronic 4 - H413	
<b>distillates (petroleum), hydrotreated light</b>	<b>5-10%</b>
CAS number: 64742-47-8                      REACH registration number: 01-2119457736-27-0001	
<b>Classification</b> Asp. Tox. 1 - H304	
<b>Pine oil</b>	<b>1-5%</b>
CAS number: 8002-09-3	
<b>Classification</b> Acute Tox. 4 - H302 Eye Irrit. 2 - H319	

## LIQUITEX SOLUVAR GLOSS VARNISH

<b>Nonane</b>	<b>1-5%</b>
CAS number: 111-84-2	REACH registration number: 01-2119463259-31-XXXX
M factor (Acute) = 1	
<b>Classification</b>	
Flam. Liq. 3 - H226	
Aquatic Acute 1 - H400	
<b>1,2,4-TRIMETHYLBENZENE</b>	<b>1-5%</b>
CAS number: 95-63-6	
<b>Classification</b>	
Flam. Liq. 3 - H226	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
STOT SE 3 - H335	
Aquatic Chronic 2 - H411	
<b>Toluene</b>	<b>&lt;1%</b>
CAS number: 108-88-3	REACH registration number: 01-2119471310-51-XXXX
<b>Classification</b>	
Flam. Liq. 2 - H225	
Skin Irrit. 2 - H315	
Repr. 2 - H361d	
STOT SE 3 - H336	
STOT RE 2 - H373	
Asp. Tox. 1 - H304	
Aquatic Chronic 3 - H412	
<b>Derivative of Benzotriazole; EC No. 400-830-7; Index No. 607-176-00-3</b>	<b>&lt;1%</b>
CAS number: —	
<b>Classification</b>	
Skin Sens. 1 - H317	
Aquatic Chronic 2 - H411	

The Full Text for all Hazard Statements are Displayed in Section 16.

#### 4. First-aid measures

##### Description of first aid measures

##### **General information**

Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.

## LIQUITEX SOLUVAR GLOSS VARNISH

<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms are severe or persist.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Get medical advice/attention if you feel unwell. Do not induce vomiting unless under the direction of medical personnel.
<b>Skin Contact</b>	Rinse with water.
<b>Eye contact</b>	Rinse with water. Get medical attention if any discomfort continues.
<b>Protection of first aiders</b>	First aid personnel should wear appropriate protective equipment during any rescue.

### **Most important symptoms and effects, both acute and delayed**

<b>General information</b>	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	No specific symptoms known.
<b>Ingestion</b>	No specific symptoms known.
<b>Skin contact</b>	Repeated exposure may cause skin dryness or cracking.
<b>Eye contact</b>	No specific symptoms known. May be slightly irritating to eyes.

### **Indication of immediate medical attention and special treatment needed**

<b>Notes for the doctor</b>	Treat symptomatically.
-----------------------------	------------------------

### **5. Fire-fighting measures**

#### **Extinguishing media**

<b>Suitable extinguishing media</b>	The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.

#### **Special hazards arising from the substance or mixture**

<b>Specific hazards</b>	Containers can burst violently or explode when heated, due to excessive pressure build-up. Flammable liquid and vapour. Vapors may be ignited by a spark, a hot surface or an ember. Vapors may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard.
-------------------------	---

<b>Hazardous combustion products</b>	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.
--------------------------------------	---

#### **Advice for firefighters**

<b>Protective actions during firefighting</b>	Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.
---	---

<b>Special protective equipment for firefighters</b>	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.
--	--

### **6. Accidental release measures**

#### **Personal precautions, protective equipment and emergency procedures**

## LIQUITEX SOLUVAR GLOSS VARNISH

**Personal precautions** Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Evacuate area. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated.

### Environmental precautions

**Environmental precautions** Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment.

### Methods and material for containment and cleaning up

**Methods for cleaning up** Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Do not allow material to enter confined spaces, due to the risk of explosion. Absorb small quantities with paper towels and evaporate in a safe place. Once evaporation is complete, place paper in a suitable waste disposal container and seal securely. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dangerous for the environment. Do not empty into drains. For waste disposal, see Section 13.

**Reference to other sections** For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

## 7. Handling and storage

### Precautions for safe handling

**Usage precautions** Keep out of the reach of children. Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists. The product is flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Suspected of damaging the unborn child. Pregnant or breastfeeding women should not work with this product if there is any risk of exposure. Avoid discharge to the aquatic environment. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.

**Advice on general occupational hygiene** Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse.

### Conditions for safe storage, including any incompatibilities

**Storage precautions** Store locked up. Keep away from oxidizing materials, heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage.

**Storage class** Flammable liquid storage.

### Specific end uses(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## 8. Exposure Controls/personal protection

### Exposure controls

## LIQUITEX SOLUVAR GLOSS VARNISH

### Protective equipment



#### Appropriate engineering controls

Provide adequate ventilation.

#### Eye/face protection

Avoid contact with eyes. Large Spillages: Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.

#### Hand protection

Wear protective gloves. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

#### Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

#### Hygiene measures

Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.

#### Respiratory protection

No specific recommendations. Provide adequate ventilation. Large Spillages: If ventilation is inadequate, suitable respiratory protection must be worn.

#### Environmental exposure controls

Keep container tightly sealed when not in use. Avoid release to the environment.

## 9. Physical and Chemical Properties

### Information on basic physical and chemical properties

Appearance	Liquid
Color	Colorless.
Odor	Characteristic.
pH	Not applicable.
Flash point	41.°C CC (Closed cup).
Upper/lower flammability or explosive limits	: 0.9
Vapour pressure	2. mm Hg @ °C
Solubility(ies)	<0.1 @ °C Insoluble in water
Auto-ignition temperature	>250°C
Viscosity	134 s @ °C
Other information	Not available.

## 10. Stability and reactivity

### Reactivity

There are no known reactivity hazards associated with this product.

### Stability

Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.

## LIQUITEX SOLUVAR GLOSS VARNISH

<b>Possibility of hazardous reactions</b>	The following materials may react strongly with the product: Oxidizing agents.
<b>Conditions to avoid</b>	Avoid heat, flames and other sources of ignition. Containers can burst violently or explode when heated, due to excessive pressure build-up. Static electricity and formation of sparks must be prevented.
<b>Materials to avoid</b>	Oxidizing materials. Acids - oxidizing.
<b>Hazardous decomposition products</b>	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

### 11. Toxicological information

#### Information on toxicological effects

##### Acute toxicity - oral

<b>Notes (oral LD<sub>50</sub>)</b>	Based on available data the classification criteria are not met.
<b>ATE oral (mg/kg)</b>	25,773.2

##### Acute toxicity - dermal

<b>Notes (dermal LD<sub>50</sub>)</b>	Based on available data the classification criteria are not met.
---------------------------------------	--

##### Acute toxicity - inhalation

<b>Notes (inhalation LC<sub>50</sub>)</b>	Based on available data the classification criteria are not met.
<b>ATE inhalation (gases ppm)</b>	266,665.09
<b>ATE inhalation (vapours mg/l)</b>	651.85
<b>ATE inhalation (dusts/mists mg/l)</b>	88.89

##### Skin corrosion/irritation

<b>Animal data</b>	Repeated exposure may cause skin dryness or cracking.
--------------------	---

##### Serious eye damage/irritation

<b>Serious eye damage/irritation</b>	Based on available data the classification criteria are not met.
--------------------------------------	--

##### Respiratory sensitisation

<b>Respiratory sensitisation</b>	Based on available data the classification criteria are not met.
----------------------------------	--

##### Skin sensitisation

<b>Skin sensitisation</b>	Based on available data the classification criteria are not met.
---------------------------	--

##### Germ cell mutagenicity

<b>Genotoxicity - in vitro</b>	Based on available data the classification criteria are not met.
--------------------------------	--

##### Carcinogenicity

<b>Carcinogenicity</b>	Based on available data the classification criteria are not met.
------------------------	--

##### **IARC carcinogenicity**

None of the ingredients are listed or exempt.

##### Reproductive toxicity

<b>Reproductive toxicity - fertility</b>	Based on available data the classification criteria are not met.
--	--

##### **Reproductive toxicity - development**

Suspected of damaging the unborn child.

##### Specific target organ toxicity - single exposure

## LIQUITEX SOLUVAR GLOSS VARNISH

**STOT - single exposure** Not classified as a specific target organ toxicant after a single exposure.

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** STOT RE 1 - H372 Causes damage to organs through prolonged or repeated exposure.

### Aspiration hazard

**Aspiration hazard** Based on available data the classification criteria are not met.

### General information

Avoid contact during pregnancy/while nursing. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

### Inhalation

No specific symptoms known.

### Ingestion

No specific symptoms known.

### Skin Contact

Repeated exposure may cause skin dryness or cracking.

### Eye contact

No specific symptoms known.

### Acute and chronic health hazards

Gas or vapor is harmful on prolonged exposure or in high concentrations.

### Route of entry

Ingestion Inhalation Skin and/or eye contact

### Target Organs

No specific target organs known.

## 12. Ecological Information

### Ecotoxicity

Dangerous for the environment. May cause long-term adverse effects in the aquatic environment.

### Toxicity

#### Toxicity

Aquatic Chronic 2 - H411 Toxic to aquatic life with long lasting effects.

#### Acute toxicity - fish

Not determined.

#### Acute toxicity - aquatic invertebrates

Not determined.

#### Acute toxicity - aquatic plants

Not determined.

#### Acute toxicity - microorganisms

Not determined.

### Persistence and degradability

#### Persistence and degradability

The degradability of the product is not known.

### Bioaccumulative potential

#### Bio-Accumulative Potential

No data available on bioaccumulation.

### Mobility in soil

#### Mobility

No data available.

### Other adverse effects

#### Other adverse effects

None known.

## 13. Disposal considerations

### Waste treatment methods



## LIQUITEX SOLUVAR GLOSS VARNISH

<b>General information</b>	The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.
<b>Disposal methods</b>	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
<b>Waste class</b>	08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances

### 14. Transport information

#### UN Number

UN No. (DOT) 1263

UN No. (IMDG) 1263

UN No. (ICAO) 1263

#### UN proper shipping name

Proper shipping name (DOT) PAINT RELATED MATERIAL

Proper shipping name (IMDG) PAINT RELATED MATERIAL

Proper shipping name (ICAO) PAINT RELATED MATERIAL

#### Transport hazard class(es)

IMDG Class 3

ICAO class/division 3

#### Transport labels



#### Packing group

DOT pack group III

IMDG packing group III

ICAO packing group III

#### Environmental hazards

Environmentally Hazardous Substance

No.

#### Special precautions for user

EmS F-E, S-E

### 15. Regulatory information

## LIQUITEX SOLUVAR GLOSS VARNISH

### **Regulatory Status**

This product has been evaluated by a toxicologist and labelled for acute and chronic health hazards in accordance with the Labelling of Hazardous Art Materials Regulation and Federal Regulation 16 CFR 1500.14 of the Federal Hazardous Substances Act. This product conforms to ASTM D-4236 Standard Practice for Labelling Art Materials for Chronic Adverse health effects.

This product has been certified by ACMI (Artists Craft Material Institute, Inc.) to carry the CL (Cautionary Labelling) Seal, meaning the following warnings and safe use instructions should be observed.

WARNING: COMBUSTIBLE. MAY BE HARMFUL IF SWALLOWED. VAPOR HARMFUL. EYE IRRITANT.

Contains: PETROLEUM DISTILLATES

PRECAUTIONS: Keep away from eyes. Avoid ingestion. Do not store or use near heat or flame. Use only with adequate ventilation. KEEP OUT OF REACH OF CHILDREN.

FIRST AID TREATMENT: If eye contact occurs, rinse with tap water for 5-10 minutes. If irritation persists, seek medical care. If inhalation symptoms occur, move to fresh air. If symptoms persist, see a physician. If swallowed, get prompt medical attention. For Health information only call 1-800-628-3385 Piscataway NJ 08855.

### **US Federal Regulations**

#### **SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities**

None of the ingredients are listed or exempt.

#### **CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)**

None of the ingredients are listed or exempt.

#### **SARA Extremely Hazardous Substances EPCRA Reportable Quantities**

None of the ingredients are listed or exempt.

#### **SARA 313 Emission Reporting**

None of the ingredients are listed or exempt.

#### **CAA Accidental Release Prevention**

None of the ingredients are listed or exempt.

#### **FDA - Essential Chemical**

None of the ingredients are listed or exempt.

#### **FDA - Precursor Chemical**

None of the ingredients are listed or exempt.

#### **SARA (311/312) Hazard Categories**

None of the ingredients are listed or exempt.

#### **OSHA Highly Hazardous Chemicals**

None of the ingredients are listed or exempt.

### **US State Regulations**

#### **California Proposition 65 Carcinogens and Reproductive Toxins**

None of the ingredients are listed or exempt.

#### **California Air Toxics "Hot Spots" (A-I)**

None of the ingredients are listed or exempt.

## LIQUITEX SOLUVAR GLOSS VARNISH

### California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed or exempt.

### California Directors List of Hazardous Substances

None of the ingredients are listed or exempt.

### Massachusetts "Right To Know" List

None of the ingredients are listed or exempt.

### Rhode Island "Right To Know" List

None of the ingredients are listed or exempt.

### Minnesota "Right To Know" List

None of the ingredients are listed or exempt.

### New Jersey "Right To Know" List

None of the ingredients are listed or exempt.

### Pennsylvania "Right To Know" List

None of the ingredients are listed or exempt.

### Inventories

#### US - TSCA

None of the ingredients are listed or exempt.

#### US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

### 16. Other information

<b>Training advice</b>	Read and follow manufacturer's recommendations.
<b>Revision date</b>	7/31/2015
<b>Revision</b>	3
<b>Supersedes date</b>	18/09/2012
<b>Hazard statements in full</b>	<p>H225 Highly flammable liquid and vapor.  H226 Flammable liquid and vapor.  H302 Harmful if swallowed.  H304 May be fatal if swallowed and enters airways.  H315 Causes skin irritation.  H317 May cause an allergic skin reaction.  H319 Causes serious eye irritation.  H332 Harmful if inhaled.  H335 May cause respiratory irritation.  H336 May cause drowsiness or dizziness.  H361d Suspected of damaging the unborn child.  H372 Causes damage to organs through prolonged or repeated exposure.  H373 May cause damage to organs through prolonged or repeated exposure.  H400 Very toxic to aquatic life.  H411 Toxic to aquatic life with long lasting effects.  H412 Harmful to aquatic life with long lasting effects.  H413 May cause long lasting harmful effects to aquatic life.</p>

## LIQUITEX SOLUVAR GLOSS VARNISH

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.